STAR HIB® HT

High-Performance Salt-Free Shale Inhibitor





DESCRIPTION

STAR HIB® HT high-performance shale inhibitor is a proprietary non-ionic amine designed for use in water-based (WBM) drilling fluids. STAR HIB HT is used in formations that contain reactive clays such as smectite and mixed layer illite/smectite. Unlike conventional shale inhibitors, STAR HIB HT does not require KCl or other salts for inhibition. STAR HIB HT does not contribute to salinity or electrical conductivity of the drilling fluid or filtrate

ADVANTAGE

Used when drilling in environmentallysensitive areas where KCl cannot be used or when low salinity needs are required

Compatible with all common WBM additives and reservoir compliant

Resistant to contaminants

Temperature stability up to 149°C (300°F)

APPLICATION

Designed for use in environmentallysensitive areas

Equally effective in fresh water-, sea water- or brine-based drilling fluid systems

ENVIRONMENTAL ADVANTAGE

Environmentally compliant for use in all areas

CEFAS and REACH registered

HMCS Category C

TREATMENT RECOMMENDATIONS

Effective at concentrations as low as 2-4 wt% for most shales and depletion rates are similar to KCl-glycol fluids

Can be mixed directly into the fluid system through the hopper, straight into the pit or gravity feed dispenser

PHYSICAL PROPERTIES

Appearance: Clear amber liquid

Specific Gravity: 1.05 g/cm³ (8.76 lb/gal)

Freezing Point: -16°C (2°F)

Water Solubility: 100% soluble

HANDLING AND STORAGE

Use appropriate PPE and review the SDS before use. Store drums upright.

PACKAGING

STAR HIB HT is available in 55 gal/210 liter drums.

DRILLING / CEMENTING / COMPLETIONS / IMPACT-FLUIDS.COM